



COMPRESSOR TECHNICAL DATA

COMPRESSOR DEFINITION

Designation	NE U6212Z
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	268GA51

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	High Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-15°C to 10°C	(5°F to 50°F)	
5 Motor type	CSIR		
6 Starting torque	HST - Hight starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	16.2	[kgf/cm ²] (230 psig)	/ °C - °F
9.2 Peak (gauge)	20.6	[kgf/cm ²] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/2	[hp]
2 Displacement	14.28	[cm ³] (0.871 cu.in)
2.1 Bore [mm]	30.157	
2.2 Stroke [mm]	20.000	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	11.14	[kg] (24.56 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	MTRP-0012	
3 Start capacitor	53-64(330)	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	T0964/G6	
6 Start winding resistance	27.92	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	4.53	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	20.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	3.90	[A] - Measured according to UL 984
11 Approval boards certification	VDE	



COMPRESSOR TECHNICAL DATA

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAEHBP46 Fan		Evaporating temperature (Condensing temperature		7.2°C (44.96°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
4845	1221	1420	628	3.81	31.41	7.72	1.95	2.26

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE46 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+5)	2334	588	684	344	3.02	12.63	6.79	1.71	1.99
-10	(+14)	2944	742	863	377	3.08	15.98	7.82	1.97	2.29
-5	(+23)	3690	930	1081	413	3.16	20.10	8.93	2.25	2.62
0	(+32)	4572	1152	1340	452	3.26	25.01	10.11	2.55	2.96
+5	(+41)	5591	1409	1638	494	3.38	30.76	11.32	2.85	3.32
+10	(+50)	6746	1700	1977	538	3.52	37.35	12.55	3.16	3.68

TEST CONDITIONS: @220V50Hz			ASHRAE46 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+5)	2042	515	598	371	3.10	11.93	5.51	1.39	1.61
-10	(+14)	2612	658	765	411	3.18	15.32	6.36	1.60	1.86
-5	(+23)	3303	832	968	453	3.27	19.45	7.29	1.84	2.14
0	(+32)	4115	1037	1206	497	3.39	24.35	8.27	2.08	2.42
+5	(+41)	5047	1272	1479	544	3.53	30.04	9.28	2.34	2.72
+10	(+50)	6101	1537	1788	593	3.69	36.56	10.30	2.59	3.02

TEST CONDITIONS: @220V50Hz			ASHRAE46 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+5)	1772	447	519	390	3.13	11.29	4.55	1.15	1.33
-10	(+14)	2283	575	669	439	3.24	14.60	5.20	1.31	1.52
-5	(+23)	2899	731	850	490	3.37	18.63	5.91	1.49	1.73
0	(+32)	3621	912	1061	543	3.52	23.39	6.67	1.68	1.95
+5	(+41)	4448	1121	1303	598	3.69	28.91	7.44	1.88	2.18
+10	(+50)	5380	1356	1576	655	3.89	35.23	8.21	2.07	2.41



COMPRESSOR TECHNICAL DATA

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.1 +0.10/+0.00	[mm]	(0.319" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	8.1 +0.10/+0.00	[mm]	(0.319" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		